NO.	NAME	LENGTH
1	6" COMPOUND METER	24"*
2	6" FLANGED x PLAIN END	12"
3	6" FLANGED COUPLING ADAPTER	5"
4	NBU 6" GATE VALVE SQUARE NUT	10.5"
5	6" x 6" x 6" FLANGED TEE	16"
6	PROPERTY OWNER'S 6" GATE VALVE SQUARE NUT	10.5"
7	6" FLANGED ELBOW 90°	
8	6" BYPASS GATE VALVE with HANDWHEEL	10.5"
9	6" BYPASS DUCTILE IRON PIPE	
10	6" FLANGED SPOOL	

^{*}DIMENSIONS- SUBJECT TO CHANGE, CHECK WITH INSPECTOR

NOTES:

- 1. PIPE AND METER SIZE SHALL BE AS DETERMINED BY OWNER; APPROVAL BY NBU WATER SYSTEMS ENGINEERING. PLANS MUST BE PREPARED BY LICENSED ENGINEER IF INSTALLATION IN RIGHT-OF-WAY IS BY OTHER THAN NEW BRAUNFELS UTILITIES FORCES.
- 2. METER VAULT MUST BE BEHIND CURB AND/OR WALK AND OUT OF VEHICULAR TRAFFIC.
- 3. MAIN LINE AND BYPASS VALVES WILL BE RESILIENT SEAT TYPE WITH CORROSION RESISTANT FUSION BONDED EPOXY COATING INSIDE AND OUTSIDE, NON-RISING STEM. MAIN LINE VALVES SHALL HAVE SQUARE OPERATING NUTS. BYPASS VALVE WILL HAVE A HANDWHEEL. PROPERTY OWNER'S VALVE MUST BE LOCATED OUTSIDE OF THE NEW BRAUNFELS UTILITIES METER VAULT.
- 4. APPROVAL WILL BE NEEDED IF HEIGHT OF VAULT EXCEEDS 72", CALL NEW BRAUNFELS UTILITIES.
- 5. HATCH OPENING WILL BE 30" X 30".
- 6. IRON PIPE TAPPING SLEEVE IN STREET RIGHT-OF-WAY SHALL BE IMBEDDED IN GRANULAR MATERIALS AS REQUIRED BY SPECIFICATIONS; BACKFILL ABOVE GRANULAR BEDDING AS REQUIRED BY SPECIFICATIONS.
- 7. DOUBLE HARNESS MJ WITH TIE RODS. ALL OTHER FITTINGS INSIDE VAULT WILL BE FLANGED.
- 8. CONTACT NEW BRAUNFELS UTILITIES PRIOR TO INSTALLATION OF COMPOUND METERS FOR PROPER DOMESTIC DEMANDS.
- 9. NOTCHES WHERE PIPING GOES THROUGH VAULT SHALL BE FILLED WITH MORTAR.
- 10. THE TOP OF THE METER VAULT SHALL BE AT AN ELEVATION SUCH THAT THE SURROUNDING GROUND SLOPES AWAY FROM THE VAULT.

	DRAWN BY: H Shadrock APPROVED BY:	STANDARD DRAWING: COMPOUND METER INSTALLATION 6" SIZE			
NEW BRAUNFELS UTILITIES WATER SYSTEMS ENGINEERING		UPDATED: 4-23-03	SCALE: N.T.S.	SHEET: 2 OF 2	DRAWING NO. 206